

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **18179**  
T.31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which the remains of original bearing trees</p> <p style="padding-left: 40px;">A fir, 57 ins. diam., bears N. 55° E., 23 lks. dist., no marks visible. (Record, 13 lks.)</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 55° W., 19 lks. dist., with scribe marks BT visible on opened blaze.</p> <p>and the remains of bearing trees mkd. by Tracy</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 22° E., 49 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir snag, 13 ins. diam., bears S. 79° E., 50 lks. dist., with scribe marks T31S R6W S20 visible on partially healed double blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 55½° W., 54 lks. dist., with healed double blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 81½° E., 60½ lks. dist., mkd. T31S R6W S17 BT.</p> <p style="padding-left: 40px;">A western red cedar, 10 ins. diam., bears S. 71½° E., 105 lks. dist., mkd. T31S R6W S20 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 13° W., 92 lks. dist., mkd. T31S R6W S19 BT.</p> <p style="padding-left: 40px;">A western red cedar, 6 ins. diam., bears N. 77½° W., 89 lks. dist., mkd. X BT.</p> <p>N. 89° 08' W. bet. secs. 18 and 19, marking and blazing the true line.</p> <p>Ascend over SE. slope, through logged area.</p>
4.80	Gravel road, 30 lks. wide, bears N. 5° W. and S. 5° E.
5.35	Spur slopes S. 40° E.; desc. over SW. slope.
17.70	Ravine, drains S. 50° W.; asc. over broken SE. slope.
19.19	<p>The E 1/16 sec. cor. of secs. 18 and 19, established and recorded by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1960, and is accepted as the corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 17½° E., 25 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 89½° W., 41½ lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p>