

# County Surveyor's Record, Douglas County, Oregon

**18180** Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
19.19	<p style="text-align: center;">E 1/16 <math>\frac{S\ 18}{S\ 19}</math> 1984</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 65½° W., 39 lks. dist., mkd. E 1/16 S19 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 05' W., beginning new measurement.</p> <p>Ascend over broken SE. slope.</p> <p>The 1/4 sec.cor. of sec. 18 and 19, perpetuated and re- corded by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1960, further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1964, monu- mented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 31 S ¼ <math>\frac{S\ 18}{S\ 19}</math> R 6 W 1965</p> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A fir, 61 ins. diam., bears S. 55° W., 33 lks. dist., with bark blaze.</p> <p>and bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">An incense cedar, 26 ins. diam., bears S. 14° E., 87 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 49 ins. diam., bears N. 25° W., 103 lks. dist., with healed blaze.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, madrone, hemlock, chinquapin, maple, and alder; undergrowth, salal, poison oak, Oregon grape, ocean spray, hazel, huckleberry, blackberry, and ferns.</p>
9.10	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 1° 35' E., bet. secs. 17 and 18.</p> <p>Ascend over SE. slope, through logged area.</p> <p>Dirt road, 20 lks. wide, bears N. 70° E. and S. 70° W.</p>
17.50	<p>Gravel road, 30 lks.wide, bears E. and S. 88° W.</p>
19.48	<p>Point for the S 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>