

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 6 W., Willamette Meridian, Oregon

18181

CHAINS

S 1/16  
S 18 | S 17  
1984

A fir, 4 ins. diam., bears N.  $62\frac{1}{4}^\circ$  E., 23 lks.  
dist., mkd. X BT.

A pine, 5 ins. diam., bears S.  $54^\circ$  W., 47 lks.  
dist., S 1/16 S18 BT.

Corner is located on ridge top, bears N.  $80^\circ$  E. and  
S.  $85^\circ$  W.

From this point the U. S. Coast and Geodetic Survey tri-  
angulation station "SILVER BUTTE", bears S.  $74^\circ 19'$  E.,  
291.22 chs. dist., monumented with a standard brass  
tablet,  $3\frac{1}{2}$  ins. diam., set in concrete, in bedrock,  
flush with the surface of the ground, with top mkd.  
SILVER BUTTE 1942.

Descend over N. slope.

38.96

The  $1/4$  sec. cor. of secs. 17 and 18 perpetuated and re-  
corded by John M. Powell, Deputy County Surveyor, in  
1965, monumented with an iron post,  $1\frac{1}{4}$  ins. diam., firm-  
ly set, projecting 17 ins. above ground, with brass cap  
mkd.

COUNTY SURVEYORS OFFICE  
T 31 S R 6 W  
S 18 | S 17  
 $\frac{1}{4}$   
1965

from which the remains of the original bearing trees

A fir snag, 16 ins. diam., bears S.  $45^\circ$  E., 11  
lks. dist., with fragmentary scribe marks visible  
on partially healed double blaze.

A sawed fir stump, 14 ins. diam., bears S.  $46^\circ$  W.,  
22 lks. dist., with healed blaze.

and new bearing trees

A fir, 21 ins. diam., bears S.  $80\frac{1}{2}^\circ$  E., 47 lks.  
dist., mkd.  $\frac{1}{4}$  S17 BT.

A fir, 7 ins. diam., bears N.  $81\frac{1}{4}^\circ$  W., 22 lks.  
dist., mkd.  $\frac{1}{4}$  S18 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, madrone, hemlock, chinquapin,  
maple, and alder; undergrowth, salal, poison oak, Oregon  
Grape, ocean spray, huckleberry, blackberry, and ferns.

Subdivision of Section 18,  
T. 31 S., R. 6 W., Willamette Meridian, Oregon

From the  $1/4$  sec. cor. of secs. 18 and 19.