

County Surveyor's Record, Douglas County, Oregon

18182

Subdivision of Section 18,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>N. 2° 16' E., on the N. and S. center line of sec. 18, marking and blazing the true line.</p> <p>Ascend over broken SE. slope, through moderate timber and undergrowth.</p>
19.65	<p>Point for the center S 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C S 1/16 S 18 C 1984</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears N. 86° E., 47 lks. dist., mkd. CS 1/16 S18 BT.</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears N. 52° W., 28 lks. dist., mkd. X BT.</p> <p>Ascend over broken SE. slope.</p>
26.70	<p>Dirt road, 20 lks. wide, bears N. 70° W. and S. 70° E.</p>
30.55	<p>Gravel road, 35 lks. wide, bears E. and S. 70° W.</p>
31.75	<p>Junction of dirt roads. 30 lks. wide, bear N. 65° W., S. 65° E., and W.</p>
39.30	<p>Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 31 S R 6 W C ¼ S 18 1984</p> </div> <p>from which</p> <p style="margin-left: 40px;">A pine, 4 ins. diam., bears S. 32½° E., 35 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears N. 40° W., 289 lks. dist., mkd. C ¼ S18 BT.</p> <p>Descend over broken NE. slope.</p>
48.60	<p>Dirt road, 20 lks. wide, bears N. 85° W. and S. 85° E.</p>
77.42	<p>The ¼ sec. cor. of sec. 7 and 18, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with the original corner tree, a fir, 23 ins. diam., with scribe marks S visible on opened blaze, from which a reference monument and the remains of bearing trees mkd. by Powell</p> <p style="margin-left: 40px;">An iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, bears North, 0.02 chs. dist., with brass cap mkd. COUNTY SURVEYORS OFFICE T31S R6W ¼ S7 S18 1966.</p>