

County Surveyor's Record, Douglas County, Oregon

18183

Subdivision of Section 18
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS													
	<p>A fir snag, 21 ins. diam., bears N. 53½° E., 70 lks. dist., with healed blaze.</p> <p>A sawed fir stump, 24 ins. diam., bears S. 30° W., 29½ lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 17 ins. diam., bears N. 62½° E., 34 lks. dist., mkd. ¼ S7 BT.</p> <p>No suitable tree available in sec. 18.</p>												
	<p>From the ¼ sec. cor. of secs. 17 and 18.</p> <p>N. 88° 34' W., on the E. and W. center line of sec. 18.</p> <p>Descend over broken NW. slope.</p>												
6.00	<p>Creek, 4 lks. wide, course N. 5° W.; asc. over broken NE. slope.</p>												
18.96	<p>Point for the center E 1/16 sec. cor. of secs. 18.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">C</td> <td style="border-top: 1px solid black; border-bottom: 1px solid black; padding: 0 10px;">E 1/16</td> <td style="padding: 0 10px;">C</td> </tr> <tr> <td></td> <td style="text-align: center; padding: 0 10px;">S 18</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center; padding: 0 10px;">1984</td> <td></td> </tr> </table> </div> <p>A fir, 5 ins. diam., bears S. 42¼° E., 316 lks. dist., mkd. CE 1/16 S18 BT.</p> <p>A fir, 13 ins. diam., bears S. 37° W., 209 lks. dist., mkd. CE 1/16 S18 BT.</p> <p>Ascend over broken NE. slope.</p>	C	E 1/16	C		S 18			1984				
C	E 1/16	C											
	S 18												
	1984												
20.70	<p>Dirt road, 20 lks. wide, bears N. 70° W. and S. 60° E.</p>												
37.92	<p>The center ¼ sec. cor. of sec. 18.</p> <p>Ascend over broken NE. slope.</p>												
43.80	<p>Ridge bears N. 5° W. and S. 5° E.; also dirt road, 20 lks. wide, bears same; desc. voer broken NW. slope.</p>												
50.05	<p>Gravel road, 15 lks. wide, bears N. 10° E. and S. 20° W.</p>												
79.30	<p>Gravel road, 30 lks. wide, bears N. 30° E. and S. 10° W.</p>												
80.83	<p>The ¼ sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td style="padding: 0 5px;">S 13</td> <td style="text-align: center; padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 18</td> </tr> <tr> <td style="padding: 0 5px;">R 7 W</td> <td style="text-align: center; padding: 0 5px;"> </td> <td style="padding: 0 5px;">R 6 W</td> </tr> <tr> <td style="padding: 0 5px;">T</td> <td style="text-align: center; padding: 0 5px;">31 S</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center; padding: 0 5px;">1969</td> <td></td> </tr> </table> </div> <p>from which the remains of a bearing tree mkd. by Jelley</p>	S 13		S 18	R 7 W		R 6 W	T	31 S			1969	
S 13		S 18											
R 7 W		R 6 W											
T	31 S												
	1969												