

County Surveyor's Record, Douglas County, Oregon

18188

T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and others calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. Those lines not forming a closure were measured twice.

The geographic position of the closing corner of sections 4 and 5, on the north boundary of the township, determined by a tie to a control point, established by the doppler method of global positioning, using Magnavox MX-1502 Receivers, in 1985, is as follows:

Latitude 43° 41' 35.84" N. Longitude 123° 47' 07.31" W.

The mean magnetic declination is 19 3/4° E.

Dependent Resurvey of a Portion of the South Boundary,
T.21 S., R. 9 W. Willamette Meridian, Oregon

(Restoring the survey by Alonzo Gesner, in 1894)

Beginning at the cor. of secs. 32 and 33 only, recovered and recorded by Vernon W. Hosford, Registered Land Surveyor No. 253, in 1954, for the Evans Products Co., determined from the remains of the original bearing trees:

A decayed fir snag, 22 ins. diam., bears
S. 36° E., 102 lks. dist., no marks visible.
(Record, S. 37° E., 104 lks.)

A sawed fir stump, 22 ins. diam., bears
S. 34½° W., 99 lks. dist., with old axe marks
visible on opened blaze.

A sawed fir stump, 47 ins. diam., bears N. 71° W.,
105 lks. dist., no marks visible. (Record,
N. 58° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins.
in the ground, to solid rock, and in a mound of stone,
4 ft. base, to top, with brass cap mkd.

T 21 S R 9 W
S 32 | S 33
1985

from which new bearing trees

A fir, 10 ins. diam., bears N. 72° E., 11
lks. dist., mkd. T21S R9W S33 BT.

A fir, 10 ins. diam., bears N. 38½° W., 71
lks. dist., mkd. T21S R9W S32 BT.

The corner is located on a small spur, sloping S.