

# County Surveyor's Record, Douglas County, Oregon

**18190** Dependent Resurvey of a Portion of the South Boundary  
T. 21 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 37 ins. diam., bears S.  $24\frac{1}{2}^\circ$  E.,  $41\frac{1}{2}$  lks. dist., mkd. X BT.

A fir, 36 ins. diam., bears S.  $79\frac{3}{4}^\circ$  W., 103 lks. dist., mkd.  $\frac{1}{2}$  S5 BT.

Ascend over SE. slope.

- 17.25 Spur, slopes S.  $25^\circ$  E.; desc. over SW. slope.
- 18.35 Creek, 2 lks. wide, course S.  $40^\circ$  E.; asc. over NE. slope.
- 21.85 Wells Creek access road, asphalt surface, 30 lks. wide, bears N.  $40^\circ$  W. and S.  $30^\circ$  E.; also slope changes to general E. slope.
- 39.60 Spur ridge, bears N.  $30^\circ$  W. and S.  $20^\circ$  E.; desc. over SW. slope.
- 40.03 The cor. of secs. 31 and 32 only, monumented with an iron post,  $1\frac{1}{2}$  ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 21 S  
S 31 | S 32 R 9 W  
S 5  
T 22 S  
1971

from which the remaining original bearing tree

A fir, 56 ins. diam., bears S.  $73^\circ$  E., 195 lks. dist., with healed blaze.

and bearing trees mkd. by John M. Powell, deputy County Surveyor, in 1971.

A fir, 22 ins. diam., bears N.  $83^\circ$  E.,  $33\frac{1}{2}$  lks. dist., with healed blaze.

A fir, 11 ins. diam., bears S.  $21^\circ$  E., 23 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears N.  $14\frac{1}{2}^\circ$  W.,  $36\frac{1}{2}$  lks. dist., with healed blaze. (Record, N.  $13^\circ$  W.,  $37\frac{1}{2}$  lks.)

From this point, the closing cor. of secs. 5 and 6, T. 22 S., R. 9 W., bears N.  $89^\circ 53'$  W., 3.11 chs. dist., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 21 S R 9 W  
S 31  
S 6 | S 5  
CC  
T 22 S R 9 W  
1977

from which bearing trees mkd. by Wofford, Rogers, and Chatters