

County Surveyor's Record, Douglas County, Oregon

18192 Dependent Resurvey of a Portion of the Subdivisional Lines, T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS					
	Ascend over SE. slope, through heavy timber and dense undergrowth.				
3.775	<p>Point for the crossing closing cor. of secs. 4 and 5, at intersection with the N. bdy. of Donation Land Claim No. 39.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p><i>FD. OK BY EKELUND</i> T 22 S R 9 W</p> <p><i>8/92 1992-0034</i> CCC</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">C 39</td> <td style="padding: 0 5px;"></td> </tr> </table> <p>1985</p> </div> <p>from which</p> <div style="margin-left: 40px; margin-top: 10px;"> <p>A fir, 10 ins. diam., bears S. 83° E., 26 lks. dist., mkd. T22S R9W S4 CCC BT.</p> <p>A fir, 8 ins. diam., bears N. 7° W., 19 lks. dist., mkd. T22S R9W S5 CCC BT.</p> </div> <p>From this point, the NE. cor. of Donation Land Claim No. 39, bears S. 89° 16' E., 0.040 chs. dist., hereinafter described.</p> <p>Ascend over SE. slope.</p>	S 5	S 4	C 39	
S 5	S 4				
C 39					
4.95	Top of ascent, slopes SE.; desc. over NE. slope.				
9.30	Bottom of descent, slopes N. 45° E.; asc. over SE. slope, changing to S. slope.				
29.00	Spur ridge, bears NE. and SW.; desc. over broken NW. slope.				
36.09	<p>The ¼ sec. cor. of sec. 4 only, established by proportionate measurement and recorded by Vernon W. Hosford, Registered Land Surveyor No. 253, in 1954, for the Evans Products Co., when the original 1/4 sec. cor. of sec. 5 only was still in existence, and is accepted as the corner, monumented with a decayed wood post, 2 ins. diam., loosely set, projecting 2 ft. above ground, from which bearing trees mkd. by Hosford:</p> <div style="margin-left: 40px; margin-top: 10px;"> <p>A fir, 31 ins. diam., bears N. 47¼° E., 87 lks. dist., with healed blaze.</p> <p>A root, 10 ins. diam., of a fir, 60 ins. diam., bears S. 35° E., 6 lks. dist., with healed blaze.</p> </div> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 S R 9 W</p> <p style="margin-left: 100px;"> ¼ S 4</p> <p>1985</p> </div>				