

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 22 S., R. 9 W., Willamette Meridian, Oregon

18193

CHAINS	
	<p>from whcih a new bearing tree and bearing object</p> <p style="padding-left: 40px;">An alder, 5 ins. diam., bears S. 79° E., 53 lks. dist., mkd. $\frac{1}{4}$ S4 BT.</p> <p style="padding-left: 40px;">The marks X B0 on rock face, bears South, 1 lk. dist.</p> <p>The corner is located on shelf of steep rock face, 35 ft. high, sloping NW.</p> <p>Descend over NW. slope.</p>
39.90	<p>Ravine, drains N. 80° W.; asc. over steep, rocky SW. slope.</p>
40.38	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 5 only, determined by the method of irregular boundaries, based on the 1954 record by Vernon W. Hosford, Registered Land Surveyor No. 253, when this corner was still in existence; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 S R 9 W</p> <p>$\frac{1}{4}$ S 5 </p> <p>1985.</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 59° W., 51 lks. dist., mkd. $\frac{1}{4}$ S5 BT.</p> <p style="padding-left: 40px;">A fir, 44 ins. diam., bears N. 14° W., 33 lks. dist., mkd. $\frac{1}{4}$ S5 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 01' E., beginning new measurement.</p> <p>Ascend over steep and rocky SW. slope.</p>
3.85	<p>Spur, slopes N. 70° W.; desc. over steep NW. slope.</p>
11.50	<p>Ravine, drains S. 85° W.; asc. over SW. slope.</p>
15.665	<p>Point for the N 1/16 sec. cor. of sec. 4 only.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p> N 1/16</p> <p> S 4</p> <p>1985</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 16° E., 35 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 51° E., 33 lks. dist., mkd. N 1/16 S4 BT.</p>