

County Surveyor's Record, Douglas County, Oregon

18194 Dependent Resurvey of a Portion of the Subdivivisional Lines, T.22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Ascend over SW. slope.

21.70 Spur, slopes W.; desc. over steep NW. slope.

28.90 Ravine, drains S. 80° W.; asc. over SW. slope.

33.61 Intersect the S. bdy. of sec. 32, T. 21 S., R. 9 W.; true point for the closing cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S R 9 W
 S 32
 S 5 | S 4
 T 22 S R 9 W
 CC
 1985

from which

A fir, 6 ins. diam., bears S. 72° E., 56 lks. dist., mkd. X BT.

A fir, 6 ins. diam., bears S. 75° W., 66 lks. dist., mkd. T22S R9W S5 CC BT.

From this point, the original closing cor. of secs. 4 and 5, bears N. 0° 01' E., 0.139 chs. dist., recovered and recorded by Vernon W. Hosford, Registered Land Surveyor NO. 253, in 1954, for the Evans Products Co., and perpetuated and recorded by L. E. Monrean, Deputy County Surveyor, in 1975, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 3 ins. above ground, (alongside of which is the original sandstone 14 x 12 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. CC on S. face), with brass cap mkd.

COUNTY SURVEYORS OFFICE
 T 21 S R 9 W
 S 32
 S 5 | S 4
 T 22 S R 9 W
 1975

from which the remains of the original bearing trees

A fir, 40 ins. diam., bears N. 20½° E., 42 lks. dist., with scribe marks 9W S25 visible on opened blaze.

A sawed fir stump, 39 ins. diam., bears S. 71½° E., 101 lks. dist., with scribe marks BT visible on opened blaze. (Record, 103 lks..)

A fir, 36 ins. diam., bears S. 52° W., 175 lks. dist., with healed blaze.

Add marks AM to brass cap.

From this same point, the cor. of secs. 32 and 33 only, T. 21 S., R. 9 W., bears N. 89° 51' E., 9.08 chs. dist., hereinbefore described.

From this same point, a control point at latitude 43° 41' 51.94" N. and longitude 123° 46' 59.66" W., established in conjunction with this survey, bears N. 19° 02' E., 26.126 chs. dist., monumented with an iron rod, 36 ins. long, 5/8 in. diam., firmly set in concrete, 36 ins. in the ground, with aluminum cap mkd.