

County Surveyor's Record, Douglas County, Oregon

18197

Subdivision of Section 5
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

From the 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 22 S
 $\frac{S 5}{S 8} \frac{1}{4}$
 R 9 W
 1975

from which the remains of the original bearing trees

A decayed fir stump, 56 ins. diam., bears N. $55\frac{1}{2}^\circ$ E., 62 lks. dist., with healed blaze.

A decayed fir stump, 40 ins. diam., bears S. 9° W., 23 lks. dist., with scribe marks $\frac{1}{4}$ visible on opened blaze.

and bearing trees mkd. by Gary L. Langlitz, Deputy County Surveyor, in 1975

A fir, 18 ins. diam., bears S. 74° W., $35\frac{1}{2}$ lks. dist., with healed blaze.

A fir, 8 ins. diam., bears N. 45° W., 52 lks. dist., with healed blaze.

N. $0^\circ 46'$ W., on the N. and S. center line of sec. 5.

Ascend over SW. slope, through heavy timber and dense undergrowth.

3.465 Point for the crossing closing cor. of the N. and S. center line of sec. 5, at intersection with the N. bdy. of Donation Land Claim No. 39.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

FD. BY EKELUND 3/92
 1792-0034

T 22 S R 9 W
 C
 $\frac{CCC | S 5}{C}$
 C39
 1985

from which

A fir, 12 ins. diam., bears N. $36\frac{1}{2}^\circ$ E., 38 lks. dist., mkd. T22S R9W S5 CCC BT.

A fir, 22 ins. diam., bears N. $47\frac{1}{2}^\circ$ W., $60\frac{1}{2}$ lks. dist., mkd. X BT.

Ascend over SW. slope.

4.30 Spur, slopes W.; desc. over NW. slope.