

# County Surveyor's Record, Douglas County, Oregon

18198

Subdivision of Section 5,  
T 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
8.90	Creek, 1 lk. wide, course W.; asc. over SW. slope.
20.10	Spur, slopes W.; desc. over NW. slope.
29.65	Wells Creek, 20 lks. wide, course S. 50° W.; asc. over SE. slope.
39.485	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 5, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W C <math>\frac{1}{4}</math> S 5 1985</p> <p>from which</p> <p style="margin-left: 40px;">A fir, 58 ins. diam., bears N. 40<math>\frac{1}{2}</math>° E., 227 lks. dist., mkd. C <math>\frac{1}{4}</math> S5 BT.</p> <p style="margin-left: 40px;">A fir, 36 ins. diam., bears N. 18° W., 153 lks. dist., mkd. C <math>\frac{1}{4}</math> S5 BT.</p> <p>Continue over nearly level land.</p>
41.25	Creek, 2 lks. wide, course S. 60° E.; asc. over SE. slope.
59.07	<p>Point for the center N 1/16 sec. cor. of sec. 5.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16   S 5 C 1985</p> <p>from which</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears S. 40<math>\frac{1}{2}</math>° E., 62 lks. dist., mkd. CN 1/16 S5 BT.</p> <p style="margin-left: 40px;">A hemlock, 20 ins. diam., bears S. 81<math>\frac{1}{2}</math>° W., 36<math>\frac{1}{2}</math> lks. dist., mkd. CN 1/16 S5 BT.</p> <p>Ascend over SE. slope.</p>
65.40	Top of ascent, slopes E.; desc. over NE. slope.
69.90	Creek, 1 lk. wide, course E.; asc. over SE. slope.
73.15	The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the tp.