

County Surveyor's Record, Douglas County, Oregon

18199

Subdivision of Section 5,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>From the 1/4 sec. cor. of sec. 5 only, on the E. bdy. of the section.</p> <p>S. 89° 53' W., on the E. and W. center line of sec. 5.</p> <p>Descend over SW. slope, through heavy timber and dense undergrowth.</p>
5.00	Ravine, drains N. 60° W.; desc. over NW. slope.
10.20	Bottom of descent, slopes N.; asc. over NE. slope.
19.50	Spur, slopes N. 10° W.; desc. over NW. slope.
33.00	Wells Creek, 13 lks. wide, course S. 30° W.; asc. over SE. slope.
39.43	The center 1/4 sec. cor. of sec. 5.
45.90	Wells Creek access road, asphalt surface, 30 lks wide, bears N. 10° W. and S. 10° E.
56.15	Spur, slopes S.; desc. over SW. slope.
66.35	Ravine, drains S. 30° E.; asc. over SE. slope.
66.95	Small spur, slopes S. 25° E.; desc. over SW. slope.
67.90	Creek, 10 lks. wide, course S. 20° E.; asc. over NE. slope, changing to SE. slope.
73.41	<p>The 1/4 sec. cor. of sec. 5 only, on the W. bdy. of the sec. monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 S R 9 W</p> <p style="margin-left: 100px;"> ¼ S 5</p> <p style="margin-left: 100px;">1983</p> </div> <p>from which bearing trees mkd. by Wofford, Rogers, and Chatters.</p> <p style="margin-left: 40px;">A fir, 44 ins. diam., bears N. 19½° E., 93 lks. dist., with healed blaze. (Record, N. 18½° E.)</p> <p style="margin-left: 40px;">A hemlock, 14 ins. diam., bears S. 18½° E., 95 lks. dist., with scribe marks ¼ S5 BT visible on partially healed blaze. (Record, S. 19½° E.)</p>
	<p>From the center N 1/16 sec. cor. of sec. 5.</p> <p>N. 89° 49' W., on the E. and W. center line of the NW 1/4 of sec. 5.</p> <p>Ascend over broken SE. slope, through heavy timber and dense undergrowth.</p>
3.95	Wells creek access road, asphalt surface, 30 lks. wide, bears N. and S. 10° W.
26.95	Spur, slopes S. 10° E.; desc. over SW. slope.
34.00	The N 1/16 sec. cor. of sec. 5 only, on the W. bdy. of the section, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.