

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary
 (Sixth Standard Parallel South),
 18204 T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

and a bearing tree mkd. by Bryon

A madrone, 10 ins. diam., bears S. 84° E., 32 lks.
 dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins.
 diam., 6 ins. in the ground, to solid rock, directly
 over iron rod, in a mound of stone, 4 ft. base to top,
 with brass cap mkd.

SC
 T 27 S R 3 W
 ½ S 35
 1985

from which a new bearing tree

A fir, 7 ins. diam., bears N. 59½° E., 68 lks.
 dist., mkd. ¼ S35 SC BT.

Deposit white "DEEP-1" magnetic marker at base of
 stainless steel post.

From this point, a point established by person(s)
 unknown, bears N. 89° 53' E., 0.20 chs. dist.
 monumented with an iron rod, ¾ in. diam., firmly set,
 projecting 12 ins. above ground.

S. 89° 45' W., beginning new measurement.

Descend over broken SW. slope, along S. edge of timber
 bears E. and W.

19.48 Point for the standard W 1/16 sec. cor. of sec. 35
 only.

Set a stainless steel post, 28 ins. long, 2½ ins.
 diam., 25 ins. in the ground, with brass cap mkd.

SC
W 1/16 S 35
 1985

from which

A grand fir, 10 ins. diam., bears N. 34° E., 14
 lks. dist., mkd. W 1/16 S35 SC BT.

A fir, 5 ins. diam., bears N. 19½° W., 35 lks.
 dist., mkd. X BT.

Descend over broken SW. slope.

21.95 Gravel road, 20 lks. wide, bears N. 25° W. and
 S. 25° E.