

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary  
(Sixth Standard Parallel South).  
T 27 S., R. 3 W., Willamette Meridian, Oregon

18205

CHAINS	
30.75	Cavitt Creek, 50 lks. wide, course N. 30° W.; asc. over SE. slope.
38.96	<p>The standard cor. of secs. 34 and 35, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 15 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">U.S.P.C. PROPERTY COR. T 27 S R 3 W <u>34   35</u> RE 4287</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed cedar stump, 30 ins. diam., bears N. 60° E., 53 lks. dist., with rotted blaze. (Record, 50 lks.)</p> <p>and the remains of bearing trees mkd. by Corbin</p> <p style="padding-left: 40px;">A cedar snag, 9 ins. diam., bears N. 2 3/4° E., 299 lks. dist., with scribe marks T27S R3W SC BT visible on partially healed blaze. (Record, N. 2° E.)</p> <p style="padding-left: 40px;">A cedar snag, 12 ins. diam., bears N. 67 3/4° W., 155 lks. dist., with scribe marks T27S R3W S34 SC BT visible on partially healed blaze. (Record N. 68 1/2° W.)</p> <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1962</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears N. 62° W., 127 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 17 ins. diam., bears N. 6 3/4° E., 238 lks. dist., mkd. T27S R3W S35 SC BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, madrone, hemlock, chinquapin, maple, and alder; undergrowth, salal, poison oak, Oregon grape, ocean spray, huckleberry, blackberry, and ferns.</p>
<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W., Willamette Meridian, Oregon</p>	
<p>(Restoring the survey by Samuel C. Flint, in 1882)</p> <hr style="width: 20%; margin: auto;"/>	
	<p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 1° 51' E., bet. secs. 35 and 36, marking and blazing the true line</p> <p>Ascend over steep S. slope, through young timber and moderate undergrowth.</p>
6.50	Spur, slopes S. 30° W.; desc. over NW. slope.
16.95	Bottom of descent, drains NW; asc. SW. slope.