

# County Surveyor's Record, Douglas County, Oregon

18206

Dependent Resurvey of a Portion of  
the Subdivisional Lines,  
T 27 S., R. 3 W., Willamette Meridian, Oregon

**CHAINS**

27.30

Spur, slopes W.; desc. over NW. slope.

39.20

The 1/4 sec. cor. of secs. 35 and 36, determined from the remains of the original bearing trees:

A maple stump, 16 ins. diam., bears N. 53 3/4° E., 12 lks. dist., with a rotted blaze and old axe marks in overgrowth. (Record, N. 30° E.)

A fir, 20 ins. diam., bears S. 31° W., 22 lks. dist., with scribe marks BT visible on opened blaze. (Record, S. 25° W.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, in a mound of stone, 3 ft base, to top, with brass cap mkd.

T 27 S R 3 W  
    1/4  
    S 35 | S 36  
    1985

from which new bearing trees

A fir, 19 ins. diam., bears S. 64 3/4° E., 77 lks. dist., mkd. 1/4 S36 BT.

A fir, 14 ins. diam., bears N. 16 1/4° W., 34 1/2 lks. dist., mkd. 1/4 S35 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, madrone, hemlock, chinquapin, maple, and alder; undergrowth, salal, poison oak, Oregon grape, ocean spray, huckleberry, blackberry, and ferns.

From the cor. of secs. 23, 24, 25, and 26, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1947, and further perpetuated and recorded by Gary L. Langlitz, Deputy County Surveyor, in 1975, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 27 S  
S 25 | S 26  
S 24 | S 23  
R 3 W

(Note: This cap is upside down and the marks are stamped to be read facing south.)

from which the remains of the original bearing trees

A sawed fir stump, 48 ins. diam., bears N. 12 3/4° E., 115 lks. dist., with scribe marks BT visible on bark blaze. (Record, N. 22° E.)