

County Surveyor's Record, Douglas County, Oregon

18207

Dependent Resurvey, Portion of Subdivisional Lines,
T 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 20° W., 53 lks. dist., with a down sawed fir stump, alongside, 34 ins. diam., with scribe marks T27S R3W S23 BT visible on bark blaze. (Record, N. 30° W.)

and bearing trees mkd. by Langlitz

A fir, 27 ins. diam., bears S. 1/2° E., 81½ lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A hemlock, 8 ins. diam., bears N. 84° W., 23 lks. dist., with scribe marks T27S R3W S23 BT visible on partially healed double blaze.

and a new bearing tree

A hemlock, 13 ins. diam., bears S. 41¼° W., 99 lks. dist., mkd. T27S R3W S26 BT.

N. 0° 23' E., bet. secs. 23 and 24.

Descend over NE. slope, along E. edge of timber, bears N. and S.

2.10 Creek, 1 lk. wide, course NW.; asc. over SW. slope.

4.65 Spur, slopes NW.; desc. over broken NW. slope.

30.40 Enter swamp, edge bears N. 30° W. and S. 30° E.

31.80 Leave swamp, edge bears N. 30° W. and S. 30° E.

41.10 The 1/4 sec. cor. of secs. 23 and 24, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1947, further perpetuated and recorded by Gregory E. Quibell, Deputy County Surveyor, in 1981, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE .

¼ S
23|24

from which the remains of the original bearing trees

A fir, 36 ins. diam., bears N. 43° E., 28 lks. dist., with healed blaze.

A cedar snag, 28 ins. diam., bears N. 78° W., 25 lks. dist., with healed blaze.

and bearing trees mkd. by Quibell

A fir, 7 ins. diam., bears S. 27° E., 31 lks. dist., with scribe marks ¼ S24 CS BT on partially healed blaze.

A fir, 9 ins. diam., bears N. 45° W., 28½ lks. dist., with scribe marks S23 BT visible on partially healed blaze.

A fir, 12 ins. diam., bears N. 13° W., 14 lks. dist., with fragmentary scribe marks visible on pitched over blaze.