

# County Surveyor's Record, Douglas County, Oregon

**18208** Dependent Resurvey, Portion of Subdivisional Lines,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS											
	N. 0° 33' E., beginning new measurement.										
	Descend over NE. slope.										
2.70	Evarts Creek, 7 lks. wide, course N. 60° W.; asc. over broken SW. slope.										
12.85	Gravel road, 25 lks. wide, bears NW. and SE.										
20.87	Point for the N 1/16 sec. cor. of secs. 23 and 24.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">N 1/16</td></tr> <tr><td>S 23</td><td>S 24</td></tr> <tr><td colspan="2">1985</td></tr> </table> </div>	N 1/16		S 23	S 24	1985					
N 1/16											
S 23	S 24										
1985											
	from which										
	A madrone, 9 ins. diam., bears S. 45° E., 31½ lks. dist., mkd. N. 1/16 S24 BT.										
	A fir, 13 ins. diam., bears S. 77° W., 41½ lks. dist., mkd. N. 1/16 S23 BT.										
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.										
	Ascend over SW. slope.										
41.74	The cor. of secs. 13, 14, 23, and 24, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1945, and further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1969, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">COUNTY SURVEYORS OFFICE</td></tr> <tr><td colspan="2">T 27 S R 3 W</td></tr> <tr><td>S 14</td><td>S 13</td></tr> <tr><td>S 23</td><td>S 24</td></tr> <tr><td colspan="2">1969</td></tr> </table> </div>	COUNTY SURVEYORS OFFICE		T 27 S R 3 W		S 14	S 13	S 23	S 24	1969	
COUNTY SURVEYORS OFFICE											
T 27 S R 3 W											
S 14	S 13										
S 23	S 24										
1969											
	from which the remains of an original bearing tree										
	A sawed fir stump, 34 ins. diam., bears S. 35° E., 49½ lks. dist., with scribe marks T 2 S 3 S24 visible on bark blaze. (Record, 47 lks.)										
	and the remains of bearing trees mkd. by Irving										
	A fir, 35 ins. diam., bears N. 45° E., 6 lks. dist., with healed blaze.										
	A sawed fir stump, 24 ins. diam., bears S. 43¼° W., 64 lks. dist., no marks visible.										
	A fir, 16 ins. diam., bears N. 20° W., 43 lks. dist., with healed blaze.										
	and bearing trees mkd. by Vernon										
	A fir, 12 ins. diam., bears S. 49° E., 58 lks. dist., with healed blaze.										
	A fir, 15 ins. diam., bears S. 83½° W., 40½ lks. dist., with healed blaze.										