

County Surveyor's Record, Douglas County, Oregon

18210 Dependent Resurvey, Portion of Subdivisinal Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

from which

A maple, 44 ins. diam., bears N. 65° E., 55 lks. dist., mkd. N 1/16 S35 BT.

A cedar, 12 ins. diam., bears S. 88° W., 30 lks. dist., mkd. N 1/16 S34 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Ascend over broken SE. slope.

64.35 Gravel road, 30 lks. wide, bears N. 20° E. and S. 20° W.

69.00 Top of ascent, begin descent over gentle NE. slope.

70.85 Cavitt Creek, 35 lks. wide, course NW.; asc. over broken S. slope.

73.15 Gravel road, 25 lks. wide, bears NW. and SE.

80.90 The cor. of secs. 26, 27, 34, and 35, referenced by Thomas E. Shrum, Registered Engineer, No. 4287, in 1957, from original evidence no longer in existence, perpetuated and recorded by Shrum, in 1963, and further perpetuated and recorded by Ronald G. Geisler, Registered Land Surveyor, No. 1988, in 1984, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd.

RE	4	T	27	S
	2	27	26	R
	8	34	35	3
	7			W

from which the remains of bearing trees mkd. by Shrum

A sawed cedar stump, 36 ins. diam., bears N. 74° E., 130 lks. dist., with scribe marks S26 RE 4287 Bt visible on open blaze.

A sawed fir stump, 21 ins. diam., bears S. 38° E., 64 lks. dist., no marks visible.

A yew snag, 9 ins. diam., bears S. 83° W., 96½ lks. dist., with scribe marks S34 RE 4287 BT visible on open blaze.

and bearing trees mkd. by Geisler

A fir, 7 ins. diam., bears N. 81° E., 108 lks. dist., with scribe marks T27S R3W S26 BT visible on open blaze.

A fir, 6 ins. diam., bears S. 31¼° E., 121½ lks. dist., with scribe marks T27S R3W S35 BT visible on open blaze.

A fir, 9 ins. diam., bears S. 71½° W., 73 lks. dist., with scribe marks T27S R3W S34 BT visible on open blaze.