

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **18211**
 T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
 Soil, rocky clay.
 Timber, fir, pine, madrone, hemlock, maple, chinquapin,
 and alder; undergrowth, salal, poison oak, Oregon grape,
 ocean spray, huckleberry, blackberry, and ferns.

From the cor. of secs. 25, 26, 35, and 36, perpetuated
 and recorded by John M. Powell, Deputy County Surveyor,
 in 1970, and further perpetuated and recorded by Ronald G.
 Geisler, Registered Land Surveyor No. 1988, in 1984, monumented
 with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins.
 above ground, with brass cap mkd.

COUNTY SURVEYORS Office

T 27 S
 S 26 | S 25
 S 35 | S 36
 R 3 W
 1970

from which the remains of the original bearing trees

A madrone, 20 ins. diam., bears N. 80° E., 45
 lks. dist., with fragmentary marks visible from
 burned out center on overgrowth. (Record,
 N. 65° E., 47 lks.)

A sawed madrone stump, 22 ins. diam., bears
 S. 55 3/4° E., 65 lks. dist., no marks visible.
 (Record, S. 53° E., 66 lks.)

and the remains of bearing trees mkd. by Powell

A madrone, 9 ins. diam., bears N. 33° E., 16 lks.
 dist. with scribe marks T27S R3W S25 CS BT
 visible on partially healed blaze.

A sawed fir stump, 39 ins. diam., bears S. 76° E.,
 98 lks. dist., with scribe marks T27S R3W S36
 CS BT visible on partially healed blaze.

A fir, 9 ins. diam., bears S. 58° W., 12 1/2 lks.
 dist. with healed blaze.

A madrone, 7 ins. diam., bears N. 49° W., 7 lks.
 dist., with scribe marks T27S R3W S26 CS BT
 visible on partially healed blaze.

and a bearing tree mkd. by Geisler

A white oak, 6 ins. diam., bears S. 71° E., 37
 lks. dist., with scribe marks T27S R3W S36 BT
 visible on partially healed blaze.

N. 89° 11' W., bet. secs. 26 and 35.

Descend over NW. slope, through moderate timber and
 undergrowth.

33.60 Gravel road, 30 lks. wide, bears N. 35° W. and
 S. 35° E.

38.10 Buckshot Creek, 5 lks. wide, course N. 70° W.;
 continue descent over N. slope.

40.90 The 1/4 sec. cor. of sec. 26 and 35, reestablished by
 proportionate measurement and recorded by Ronald G.
 Geisler, Registered Land Surveyor, No. 1988, in 1984 and is
 accepted as the best available evidence of the original corner
 position, monumented with an iron pipe, 3/4 in. diam., firmly set
 projecting 10 ins. above ground, with an aluminum cap mkd.