

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

18213

CHAINS	
	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 87° 53' W. bet. secs. 23 and 26.</p> <p>Ascend over NE. slope, along S. edge of timber, bears E. and W., through moderate undergrowth.</p>
9.60	<p>Spur, slopes N. 30° W.; descend over W. slope.</p>
20.20	<p>Point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $E \frac{1}{16} \begin{array}{l} S \ 23 \\ S \ 26 \end{array}$ <p>1985</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears S. 29½° E., 23 lks. dist., mkd. E 1/16 S26 BT.</p> <p style="margin-left: 40px;">An incense cedar, 28 ins. diam., bears N. 12° W., 57 lks. dist., mkd. E 1/16 S23 BT.</p> <p>Descend over W. slope.</p>
40.40	<p>The ¼ sec. cor. of secs. 23 and 26, reestablished by proportionate measurement and recorded by Ben B. Irving, Deputy County Surveyor, in 1947, and recorded by Ronald G. Geisler, Registered Land Surveyor, No. 1988, in 1984, and is accepted as the best available evidence of the original corner position, monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> $\frac{1}{4} S$ $\frac{S \ 23}{S \ 26}$ </div> <p>from which bearing trees mkd. by Irving</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears S. 55° W., 20½ lks. dist., with fragmentary scribe marks visible on bark blaze.</p> <p style="margin-left: 40px;">A fir, 19 ins. diam., bears N. 39¼° W., 16 lks. dist., with scribe marks ¼ S23 CS BT on bark blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 87° 55' W., beginning new measurement.</p> <p>Descend over NW. slope.</p>
7.95	<p>Cavitt creek, 80 lks. wide, course N. 20° E.; asc. NE. slope.</p>
17.50	<p>Cavitt Creek County Road, No. 82, 35 lks. wide, bears N. 20° E. and S. 20° W.</p>
18.10	<p>Gravel road, 25 lks. wide, bears N. 55° E. and S. 55° W.</p>