

# County Surveyor's Record, Douglas County, Oregon

**18214**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

**CHAINS**

20.95

The W 1/16 sec. cor. of secs. 23 and 26, established and recorded by Ronald G. Geisler, Registered Land Surveyor, No. 1984, [sic] in 1983, and is accepted as the corner, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd.

W 1/16  $\frac{S\ 23}{S\ 26}$   
1983  
PLS 1988

from which bearing trees mkd. by Geisler

A fir, 16 ins. diam., bears N. 65½° E., 25 lks. dist., with scribe marks W 1/16 S23 BT on partially healed double blazes.

A fir, 5 ins. diam., bears S. 29½° W., 9 lks. dist., with scribe marks W 1/16 S26 BT on partially healed double blazes.

From this point, a point established by person(s) unknown, bears S. 53° 52' E., 0.106 chs. dist., monumented with a iron rod, 5/8 in. diam., firmly set, projecting 14 ins. above ground.

---

N. 87° 55' W., beginning new measurement.

Ascend over broken NE. slope.

20.96

The cor. of sec. 22, 23, 26, and 27, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor in 1947, monumented with an iron post, 1¼ ins. diam., firmly set projecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

$\frac{S\ 22}{S\ 23}$   
 $\frac{S\ 27}{S\ 26}$

from which the remains of an original bearing tree

A fir stump, 44 ins. diam., bears N. 27½° W., 50 lks. dist., with fragmentary scribe marks visible on bark blaze and with rescribed marks W S22 BT visible on bark blaze by Irving, 1947.

and the remains of bearing trees mkd. by Irving

A fir snag, 17 ins. diam., bears N. 70° E., 73½ lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A rotted fir stump, size indeterminate, bears S. 74° E., 53 lks. dist., with a downed fir alongside, with healed blaze.

and bearing trees mkd. by Jelley, in 1977