

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **18215**
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>A white oak, 11 ins. diam., bears N. 71° E., 12½ lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A white oak, 11 ins. diam., bears S. 74 3/4° E., 6½ lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A white oak, 10 ins. diam., bears S. 41 3/4° W., 69 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A white oak, 12 ins. diam., bears N. 34¼° W., 28 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, pine, hemlock, maple, madrone, alder, chinquapin, and oak; undergrowth, arrowwood, vine maple, poison oak, blackberry, huckleberry, fern, salal, Oregon grape, and young timber.</p>
20.73	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 89° 47' W., bet. secs. 14 and 23.</p> <p>Descend over broken W. slope, through heavy timber and dense undergrowth.</p> <p>The E 1/16 sec. cor. of secs. 14 and 23, established and recorded by Ben B. Irving, deputy County Surveyor, in 1947, and is accepted as the corner, monumented with a basalt stone, 24 x 14 x 8 ins., mkd. CS on W. face, loosely set in a mound of stone, 2 ft. base, from which the remains of bearing trees mkd. by Irving:</p> <p style="margin-left: 40px;">A sawed double fir stump, 60 ins. diam., bears S. 71° W., 11½ lks. dist., with scribe marks CS BT visible on a bark blaze.</p> <p style="margin-left: 40px;">A sawed fir stump, 42 ins. diam., bears N. 29° W., 43 lks. dist., with scribe marks T visible on bark blaze.</p> <p style="margin-left: 40px;">At the corner point</p> <p style="margin-left: 40px;">Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 40px;"> $E \frac{1}{16} \frac{S \ 14}{S \ 23}$ <p>1985</p> </div> <p style="margin-left: 40px;">from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 18° E., 14 lks. dist., mkd. E 1/16 S23 BT.</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 49° W., 37 lks. dist., mkd. E 1/16 S14 BT.</p> <p style="margin-left: 40px;">Deposit the corner stone alongside and white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a corner established by Thomas A. Shrum, Registered Engineer, No. 4287, during an unrecorded survey, bears N. 80½° E., 0.161 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd. T27S R3W S14 S23 E 1/16 RE 4287.</p>