

County Surveyor's Record, Douglas County, Oregon

18216 Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>S. 89° 53' W., beginning new measurement.</p> <p>Descend over broken NW. slope.</p>
20.43	<p>The ¼ sec. cor. of secs. 14 and 23, reestablished by proportionate measurement and recorded by Ben B. Irving, Deputy County Surveyor, in 1945, further perpetuated and recorded by James W. Byron, deputy County Surveyor, in 1957, recorded by Don E. Garrett, Registered Land Surveyor No. 544, in 1973, and recorded by Robert L. Dolan, Registered Land Surveyor, No. 1076, in 1985, and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 27 S R 3 W ¼ S $\frac{14}{23}$ 1957</p> <p>from which the remains of a bearing tree mkd. by Irving</p> <p style="padding-left: 40px;">A sawed fir stump, 14 ins. diam., bears N. 24° E., 33½ lks. dist., with reverse scribe marks BT. visible on overgrowth of opened blaze.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 6° E., 48 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 42 3/4° W., 73 lks. dist., with healed double blaze.</p> <p>The corner is located at intersection of wire fences, extending S. 70° E., and S., and 12 lks. south of a dirt road, 20 lks. wide, bears N. 70° W. and S. 70° E.</p> <p>From this point, the Douglas County Horizontal Control Station "BOND", bears N. 15° 11' E., 145.21 chs. dist., monumented with a brass cap 2½ ins. diam., set in a 8 ins. diam. concrete filled bell tile, 8 ins. above ground, with top mkd. DOUGLAS CO. SURVEYORS OFFICE BOND 1972.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N. 89° 51' W., beginning new measurement.</p> <p>Descend slightly over creek bottom.</p>
0.75	<p>Gravel road, 25 lks. wide, bears N. 80° W. and S. 80° E.</p>
3.60	<p>Cavitt Creek, 80 lks. wide, course N. 30° W.; sec. gentle NE. slope.</p>
6.85	<p>Cavitt creek County Road, No. 82, 30 lks. wide, bears N. 30° E. and S. 30° W.</p>
41.55	<p>The cor. of secs. 14, 15, 22, and 23, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1947, monumented with an iron post, 1½ ins. diam., firmly set, flush with the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 27 S S 15 S 14 S 22 S 23 R 3 W</p>