

# County Surveyor's Record, Douglas County, Oregon

18218

Subdivision of Section 23,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS													
	<p>A root hole bears S. 29° W., 69 lks. dist., with down fir alongside, 13 ins. diam., with healed double blaze.</p> <p>and bearing trees mkd. by Quibell</p> <p>A fir, 13 ins. diam., bears N. 41 3/4° E., 63 lks. dist., with scribe marks C 1/4 S23 CS BT visible on partially healed blaze.</p> <p>A white fir, 11 ins. diam., bears S. 3° E., 18 lks. dist., with scribe marks C 1/4 S23 CS BT visible on partially healed blaze.</p> <p>A white fir, 15 ins. diam., bears S. 32 1/2° W., 77 lks. dist., with scribe marks C 1/4 S23 CS BT visible on partially healed blaze.</p> <p>A fir, 11 ins. diam., bears N. 14° W., 52 lks. dist., with scribe marks 3 CS BT visible on partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 01' E., beginning new measurement.</p> <p>Ascend over nearly level land.</p>												
20.25	<p>The center N. 1/6 sec. cor. of sec. 23, established and recorded by Robert L. Dolan, Registered Land Surveyor, No. 1076, in 1985, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. LS 1076, from which bearing trees mkd. by Dolan:</p> <p style="padding-left: 40px;">An incense cedar, 8 ins. diam., bears N. 48 1/4° E., 76 lks. dist., with scribe marks CN 1/16 S23 BT visible on open blaze.</p> <p style="padding-left: 40px;">An Oregon ash, 17 ins. diam., bears N. 22 1/4° W., 33 lks. dist., with scribe marks CN 1/16 S23 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr><td></td><td style="text-align: center;">C</td><td></td></tr> <tr><td style="text-align: center;">N 1/16</td><td style="text-align: center;"> </td><td style="text-align: center;">S 23</td></tr> <tr><td></td><td style="text-align: center;">C</td><td></td></tr> <tr><td></td><td style="text-align: center;">1985</td><td></td></tr> </table> </div> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 02' E., beginning new measurement.</p> <p>Descend over nearly level land.</p>		C		N 1/16		S 23		C			1985	
	C												
N 1/16		S 23											
	C												
	1985												
9.80	<p>Cavitt Creek, 80 lks. wide, course N. 25° E.; asc. S. slope.</p>												
13.50	<p>Top of ascent; desc. NE. slope.</p>												
14.40	<p>Cavitt Creek, 80 lks. wide, course N. 60° W.; asc. S. slope.</p>												