

County Surveyor's Record, Douglas County, Oregon

18219

Subdivision of Section 23,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
19.85	Gravel road, 20 lks. wide, bears N. 50° W. and S. 50° E.
20.23	The ¼ sec. cor. of secs. 14 and 23.
	From the ¼ sec. cor. of secs. 23 and 24.
	N. 88° 25' W., on the E. and W. center line of sec. 23.
	Ascend over broken NE. slope, through young timber and light undergrowth.
20.39	Point for the center E 1/16 sec. cor. of sec. 23.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.
	$C \frac{E \ 1/16 \ C}{S \ 23}$ 1985
	from which
	A fir, 10 ins. diam., bears N. 56¼° E., 27 lks. dist., mkd. CE 1/16 S23 BT.
	A fir, 7 ins. diam., bears S. 57° W., 33 lks. dist., mkd. CE 1/16 S23 BT.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	Descend over broken W. slope, through heavy timber and undergrowth.
40.78	The center ¼ sec. cor. of sec. 23.
	<hr style="width: 30%; margin: 0 auto;"/>
	N. 88° 39' W., beginning new measurement.
	Descend over nearly level land.
10.05	Cavitt Creek, 80 lks. wide, course N. 30° E.; asc. over gentle E. slope.
11.70	Dirt road, 25 lks. wide, bears N. 40° E. and S. 40° W.,
14.70	Cavitt Creek County Road, No. 82, 30 lks. wide, bears N. 15° E. and S. 15° W.
20.77	The center W 1/16 sec. cor. of sec. 23, established and recorded by Ben B. Irving, Deputy County Surveyor, in 1947, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, from which the remains of bearing trees mkd. by Irving:
	A root hole, bears S. 28½° W., 17 lks. dist., with down cedar alongside, 14 ins. diam., with partially healed, rotted blaze.