

County Surveyor's Record, Douglas County, Oregon

18220

Subdivision of Section 23,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A fir, 14 ins. diam., bears N. 24° W., 15 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.

C $\frac{W \ 1/16}{S \ 23}$ C
1985

from which a new bearing tree

A cedar, 13 ins. diam., bears S. 50° E., 19 lks. dist., mkd. CW 1/16 S23 BT.

N. 88° 42' W., beginning new measurement.

Ascend over E. slope, through heavy timber and moderate undergrowth.

19.40 Dirt road, 15 lks. wide, bears NE. and SW.

20.80 The ¼ sec. cor. of secs. 22 and 23, perpetuated and recorded by Ben B. Irving, deputy County Surveyor in 1947, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

¼ | S
22 | 23
1947

from which the remains of the original bearing trees

A sawed fir stump, 26 ins. diam., bears S. 69° E., 45 lks. dist., with scribe marks ¼ S23 CS BT visible on bark blaze, facing SW. (Record S. 35° E., 37 lks.) (Note: stump moved out of true position by road construction.)

A sawed fir stump, 42 ins. diam., bears S. 60° W., 59 lks. dist., with scribe marks BT visible on bark blaze.

and new bearing trees

A grand fir, 12 ins. diam., bears S. 71½° E., 21 lks. dist., mkd. ¼ S23 BT.

A fir, 8 ins. diam., bears S. 34½° W., 45 lks. dist. mkd. ¼ S22 BT.

From the center E 1/16 sec. cor. of sec. 23.

N. 0° 03' E., on the N. and S. center line of the NE¼ of sec. 23.