

# County Surveyor's Record, Douglas County, Oregon

18221

Subdivision of Section 23,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	Ascend over gentle W. slope, through moderate timber and light undergrowth.
12.80	Spur, slopes NW.; descend over steep N. slope.
20.15	Evarts Creek, 8 lks. wide, course S. 72° W; asc. over S. slope.
20.56	Point for the NE 1/16 sec. cor. of sec. 23, at intersection with the E. and W. center line of the NE 1/4 of sec. 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.  NE 1/16 S 23 1985  from which  A fir, 8 ins. diam., bears North, 84 lks. dist. mkd. NE 1/16 S23 BT.  A boulder, 4 1/2 x 3 x 1 1/2 ft., above ground, bears N. 59 1/4° E., 11 1/2 lks. dist., mkd. X BO.  Deposit white "DEEP-1" magnetic marker at base of stainless steel post.  Ascend over S. slope.
32.35	Dirt road, 15 lks. wide, bears N. 65° W. and S. 65° E.
41.08	The E 1/16 sec. cor. of secs. 14 and 23.
	From the N 1/16 sec. cor. of secs. 23 and 24.  N. 89° 16' W., on the E. and W. center line of the NE 1/4 of sec. 23.  Descend over broken W. slope, through heavy timber and moderate undergrowth.
11.50	Dirt road, 25 lks. wide, bears N. 55° W. and S. 55° E.
20.55	The NE 1/16 sec. cor. of sec. 23.  Descend over broken W. slope.
26.25	Evarts Creek, 6 lks. wide, course N. 60° W.; asc. over broken NE. slope.
40.97	The center N 1/16 sec. cor. of sec. 23.
	From the E. 1/16 sec. cor. of secs. 23 and 26.  N. 0° 03' E., on the N. and S. center line of the SE 1/4 of sec. 23.  Descend over gentle broken W. slope, through heavy timber and light undergrowth.
40.91	The center E 1/16 sec. cor. of sec. 23.