

County Surveyor's Record, Douglas County, Oregon

18222

Subdivision of Section 23,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>From the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>N. 0° 04' E., on the N. and S. center line of the SW ¼ of sec. 23.</p> <p>Ascend over gentle broken E. slope, through heavy timber and light undergrowth.</p>
21.60	Dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W.
40.47	The center W. 1/16 sec. cor. of sec. 23.
<p>Subdivision of Section 35, T. 27 S., R. 3 W., Willamette Meridian, Oregon</p>	
	<p>From the standard ¼ sec. cor. of sec. 35 only, on the S. bdy. of the tp.</p> <p>N. 0° 43' E., on the N. and S. center line of sec. 35.</p> <p>Descend over broken W. slope, through moderate timber and undergrowth.</p>
30.55	Gravel road, 20 lks. wide, bears N. 55° W. and S. 30° E.
35.40	Same road, bears N. 55° E. and S. 55° W.
35.90	Gravel road, 25 lks. wide, bears N. 70° E. and S. 70° W.
39.86	<p>Point for the center ¼ sec. cor. of sec. 35, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., .25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 S R 3 W C ¼ S 35 1985</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 88° E., 28 dist., mkd. C ¼ S35 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 70° W., 12 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over broken W. slope.</p>
54.25	Gravel road, 20 lks. wide, bears N. 30° W. and S. 25° E.
60.00	Point for the center N 1/16 sec. cor. of sec. 35.