

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 35,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

18223

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, with top 6 ins. below surface of gravelled road, 30 lks. wide, bears N. 40° E. and S. 40° W., with brass cap mkd.</p> <p style="text-align: center;"> C N 1/16 S 35 C 1985 </p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 50 lks. dist., with brass cap mkd. CN 1/16 S35 RM 1985 33 ft. TO COR and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears East, 35 lks. dist., with brass cap mkd. CN 1/16 S35 RM 1985 23 FT TO COR and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel posts.</p> <p>Descend over broken W. slope.</p>
76.55	Creek, 1 lk. wide, course S. 70° W.; asc. over broken SW. slope.
77.20	Gravel road, 30 lks. wide, bears S. 60° E. and N. 70° W.
77.60	Gravel road, 30 lks. wide, bears N. 80° E. and N. 70° W.
80.15	The ¼ sec. cor. of secs. 26 and 35.
	<p>From the ¼ sec. cor. of secs. 35 and 36.</p> <p>N. 89° 24' W., on the E. and W. center line of sec. 35.</p> <p>Descend over broken W. slope, through heavy timber and dense undergrowth.</p>
38.40	Gravel road, 25 lks. wide, bears N. 10° W. and S. 10° E.
40.72	The center ¼ sec. cor. of sec. 35.
	Ascend over NE. slope.
49.50	Spur, slopes N. 30° W.; desc. over broken W. slope, Also gravelled road, 25 lks. wide, bears N. 30° W. and S. 30° E.
60.685	Point for the center W 1/16 sec. cor. of sec. 35.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> C — W 1/16 — C S 35 1985 </p> <p>from which</p>