

County Surveyor's Record, Douglas County, Oregon

18228 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

from which a bearing tree mkd. by Bushey

A fir, 18 ins. diam., bears S. 60½° E., 98½ lks.
dist., with illegible scribe marks visible on a
partially healed blaze.

and bearing trees mkd. by Byron

A madrone, 20 ins. diam., bears N. 70° E., 7 lks.
dist., with healed blaze.

A fir, 15 ins. diam., bears S. 71° W., 14 lks.
dist., with healed blaze.

A fir, 10 ins. diam., bears N. 41° W., 31½ lks.
dist., with healed blaze.

N. 0° 29' W., bet. secs. 21 and 22.

Ascend over a SW. slope, through heavy timber and dense
Undergrowth.

9.90 Dirt road, 15 lks. wide, on ridge top, bears N. 20° W. and
S. 20° E.; desc. over broken NE. slope.

23.60 Ravine, drains E.; asc. over SE. slope.

25.10 Spur, slopes E.; desc. over NE. slope.

36.90 Creek, 3 lks. wide, course S. 60° E.; asc. over steep SW. slope.

40.15 The ¼ sec. cor. of secs. 21 and 22, perpetuated and recorded by
James W. Byron, Deputy County Surveyor, in 1963, monumented with
an iron post, 1½ ins. diam., firmly set, projecting 15 ins. above
ground, with the original quartz stone, 12 X 12 x 6 ins., mkd. ¼
on W. face, lying alongside, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S

¼

S 21 | S 22

R 3 W

1963

from which the original bearing trees

A fir, 20 ins. diam., bears N. 42¼° E., 9 lks.
dist., with healed blaze.

A fir, 30 ins. diam., bears S. 17° W., 54½ lks.
dist., with healed blaze. (Record, 56 lks.)

North, beginning new measurement.

Ascend over a SW. slope.

15.70 Ridge, bears N. 65° E. and S. 65° W.; desc. over broken N. slope.

39.98 The cor. of secs. 15, 16, 21, and 22, monumented with an iron
post, 2½ ins. diam., firmly set, projecting 8 ins. above ground,
with brass cap mkd.

T 30 S R 3 W

S 16 | S 15

S 21 | S 22

1972