

County Surveyor's Record, Douglas County, Oregon

18229

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A root hole, bears N. 75° E., 33 lks. dist., with a decayed fir lying alongside, no visible marks.

A decayed fir stump, size indeterminate, bears S. 6¼° E., 45 lks. dist., no marks remaining.

A decayed fir stump, size indeterminate, bears S. 34 ¾° W., 47 lks. dist., with axe marks on a rotted blaze. (Record, 42½ lks.).

A root hole, bears N. 70½° W., 10 lks. dist.,

and bearing trees mkd. by Albright and Bowder

A fir, 9 ins. diam., bears N. 55½° E., 26½ lks. dist., with healed blaze.

A fir, 8 ins. diam., bears S. 41° E., 14½ lks. dist., with healed blaze.

A fir, 10 ins. diam., bears S. 28° W., 23 lks. dist., with healed blaze.

A fir, 8 ins. diam., bears N. 36½° W., 48 lks. dist., with healed blaze.

The corner is located on a steep N. slope.

From the ¼ sec. cor. of secs. 21 and 28, perpetuated and recorded by John H. Markham Jr. Registered Logging Engineer No. 2880, in 1951, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1½ ins. diam., firmly set, projecting 15 ins. above ground, (with an unmarked quartz stone, 11 x 10 x 5 ins., alongside), with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
¼ S 21
S 28
R 3 W
1963

from which the remains of the original bearing trees

A fir, 20 ins. diam., bears S. 85° W., 24 lks. dist., with healed blaze. (Record, S 80° W.)

A root crown, bears N. 80° W., 26 lks. dist., with a fir, 8 ins. diam., lying alongside, with scribe marks ¼ S visible on a rotted blaze. (Record, 23 lks.)

and bearing trees mkd. by Markham

A madrone, 20 ins. diam., bears S. 44° E., 27 lks. dist., with healed blaze.