

# County Surveyor's Record, Douglas County, Oregon

**18230** Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 3 W., Willamette Meridian, Oregon

**CHAINS**

A madrone, 22 ins. diam., bears N. 71° W., 48½  
lks. dist., with illegible bark scribing.

and a new bearing tree

A fir, 8 ins. diam., bears N. 40° W., 42 lks.  
dist., mkd. ¼ S21 BT.

The corner is located on a SE. slope, 1 ch. N. of a creek, 2 lks.  
wide, course SW.

S. 89° 27' W., bet. secs. 21 and 28.

Ascend over a SE. slope, through heavy timber and dense  
undergrowth.

3.20 Top of ascent, slopes S.; desc. over SW. slope.

4.20 Ravine, drains S.; asc. over SE. slope.

10.03 A point of which I find no record, monumented with an iron rod, ½  
in. diam., firmly set, projecting 8 ins. above the ground, with a  
plastic cap mkd. LS 866, and with a steel fence post alongside.

10.30 Top of ascent, slopes S.; desc. over SW. slope.

13.35 Underground water line, bears N. and S.

17.80 Creel. 3 lks. wide, course S.; asc. over SE. slope.

23.30 Top of ascent, slopes S.; desc. over SW. slope.

27.30 Ravine, drains S.; asc. over SE. slope.

31.00 Top of ascent; cross broken S. slope.

40.14 The cor. of secs. 20, 21, 28 and 29, perpetuated and recorded by  
John H. Markham Jr., Registered Logging Engineer No. 2880, in  
1952, monumented with an iron pipe, ½ in. diam., firmly set,  
projecting 8 ins. above the ground, from which the remains of an  
original bearing tree:

A root hole, bears N. 88° W., 129 lks. dist.,  
with a rotted oak, 20 ins. diam., lying  
alongside, no visible marks. (Record, N. 80° W.  
110 lks.)

and bearing trees mkd. by Markham

A triple trunked madrone, 40 ins. diam., bears  
S. 83° E., 40 lks. dist., with healed blaze.

A madrone, 20 ins. diam., bears S. 38° W., 8 lks.  
dist., with scribe mark S visible on a partially  
healed blaze.

A fir, 18 ins. diam., bears N. 35° W., 41 lks.  
dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 30 S R 3 W  
S 20 | S 21  
S 29 | S 28  
1986