

County Surveyor's Record, Douglas County, Oregon

18231

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which a new bearing tree</p> <p>A fir, 20 ins. diam., bears N. 55° E., 50 lks. dist., mkd. T30S R3W S21 BT.</p> <p>Deposit the iron pipe alongside and a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located at the intersection of wire fence lines, extending N. 5° E., S., and W.</p> <p>From this corner, Douglas County Surveyors Office triangulation station 911-G, at latitude 42° 56' 19.38" N. and longitude 123° 04' 47.12" W., bears S. 0° 34' E., 40.085 chs. dist., monumented with a brass cap on an iron post, 3½ ins. diam., extending 18 ins. above a 12 x 12 in. sq. concrete base. The markings on the brass cap have been damaged beyond recognition. The station is located on the southerly side of State Highway No. 227 approximately 7 road miles easterly from Days Creek, Oregon.</p>
	<p>N. 0° 04' W., bet. secs. 20 and 21.</p> <p>Ascend over S. slope, through heavy timber and dense undergrowth.</p>
4.80	<p>Spur, slopes W.; desc. over broken NW. slope.</p>
19.00	<p>Creek, 4 lks. wide, course W.; asc. over broken S. slope.</p>
39.98	<p>The ¼ sec. cor. of secs. 20 and 21, perpetuated and recorded by John H. Markham Jr., Registered Logging Engineer No. 2880, in 1951, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees:</p> <p>A root hole, bears N. 80° E., 13 lks. dist., with a rooted fir, 15 ins. diam., lying alongside, no visible marks.</p> <p>A fir, 22 ins. diam., bears S. 15° W., 24 lks. dist., with healed blaze. (Record, 28 lks.)</p> <p>and the remains of the bearing trees mkd. by Markham</p> <p>A root hole, bears N. 61° E., 24 lks. dist., with a rotted fir, 25 ins. diam., lying alongside, no visible marks</p> <p>A madrone, 13 ins. diam., bears S. 75° W., 84 lks. dist., with illegible scribe marks on a partially healed blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p>A madrone, 13 ins. diam., bears N. 58° E., 48 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 3 W ¼ S 20 S21 1986</p> <p>Deposit the iron pipe alongside and a white "DEEP-1" magnetic marker at base of stainless steel post.</p>