

County Surveyor's Record, Douglas County, Oregon

18335

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 48 ins. diam., bears N. 45° W.,
5 lks. dist., with fragmentary scribe marks
visible on burned blaze.

and the remains of bearing trees mkd. by Powell

A root hole, bears N. 31° E., 103 lks. dist., with
a down fir lying down hill, 36 ins. diam., with
fragmentary scribe marks visible on partially
healed blaze.

A sawed fir stump, 50 ins. diam., bears S. 21° E.,
114 lks. dist., with fragmentary scribe marks
visible on partially healed double blaze.

and new bearing trees

A double yew, 14 ins. diam., bears N. 36° E., 119
lks. dist., mkd. T31S R6W S8 BT.

A fir, 4 ins. diam., bears S. 20° E., 32 lks.
dist., mkd. X BT.

A fir, 4 ins. diam., bears S. 41 3/4° W., 50 lks.
dist., mkd. X BT.

Corner is located 1.10 chs. dist., East of Council Creek, 5 lks.
wide, course N. 20° E.

N. 0° 20' E., bet. secs. 7 and 8, marking and blazing the true
line.

Descend over NW. slope, through young timber and dense
undergrowth.

3.20 Council Creek, 5 lks. wide, course N. 40° E.; asc. over broken
SE. slope.

40.89 Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate
distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 31 S R 6 W
1/4
S 7 | S 8
1985

from which

A fir, 10 ins. diam., bears N. 51° E., 5 1/2 lks.
dist., mkd. 1/4 S8 BT.

A fir, 20 ins. diam., bears West, 41 lks. dist.,
mkd. 1/4 S7 BT.

Deposit white "DEEP-1" magnetic marker at base of
stainless steel post.

Ascend over broken SE. slope.

44.40 Spur, slopes N. 55° E.; desc. over NW. slope.

53.10 Creek, 5 lks wide, course N. 60° E.; asc. over broken SE. slope.

81.78 The cor. of secs. 5, 6, 7, and 8, monumented with an iron post
1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with
brass cap mkd.