

County Surveyor's Record, Douglas County, Oregon

18239

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A cedar, 21 ins. diam., bears S. 33° E.,
37 lks. dist., with healed blaze.

A cedar, 12 ins. diam., bears S. 32° W., 60 lks. dist.,
with healed blaze. (Record, S. 28° W.)

N. 0° 16' W., bet. secs. 25 and 26, marking and blazing the true
line.

Ascend over S. slope, across logged area, through light
undergrowth.

6.50 Spur, slopes SE.; desc. over NE. slope.

15.30 Ravine, drains S. 60° E.; asc. over S. slope.

20.00 The N. 1/6 sec. cor. of secs. 25 and 26, monumented with an iron
post, 2½ ins. diam., firmly set, projecting 9 ins. above ground,
with brass cap mkd.

N
Corrected 4/15/2019 W 1/16
JC DCSO S 26 S 25
1964

from which the remains of bearing trees mkd. by Brooks and
Peterson

A cedar stump, 23 ins. diam., bears S. 37° E.,
34½ lks. dist., with scribe marks 1/16 S25 BT
visible on open blaze.

A cedar stump, 9 ins. diam., bears S. 37° W.,
60 lks. dist., no marks visible.

and a new bearing tree

A fir, 9 ins. diam., bears N. 7° W., 95
lks. dist., mkd. N. 1/16 S26 BT.

No other suitable tree available.

N. 0° 02' E., beginning new measurement.

Ascend over S. slope, across logged area.

1.70 Ridge, bears E. and W.; desc. over N. slope.

19.88 The cor. of secs. 23, 24, 25 and 26, monumented with an iron
post, 2½ ins. diam., firmly set, projecting 14 ins. above ground,
with brass cap mkd.

COUNTY SURVEYORS OFFICE	
S 23 S 24	
S 26 S 25	
1960	

from which the remains of the original bearing trees

A fir stump, 44 ins. diam., bears N. 5° E.,
76 lks. dist., with healed blaze.

A fir, 17 ins. diam., bears S. 25° E., 37
lks. dist., with healed blaze.

A root hole, bears S. 25° W., 22 lks. dist.

A root hole, bears N. 10° W., 60 lks. dist., with a down
fir alongside, 16 ins. diam., no marks visible.