

County Surveyor's Record, Douglas County, Oregon

18240 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

and remains of bearing trees mkd. by James W. Byron, County Surveyor, in 1960

A fir stump, 65 ins. diam., bears S. 71° W.,
70 lks. dist., with healed blaze.

A fir stump, 22 ins. diam., bears N. 41½° W.,
85 lks. dist., with scribe marks CS BT visible
on opened blaze.

The corner is located in logged area, no suitable trees available

Land, hilly.

Soil, clay loam.

Timber, small fir reproduction; undergrowth, huckleberry, salal,
Oregon grape, blackberry, and fern.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the
Tp., monumented with an iron post, 2½ ins. diam., firmly set,
projecting 6 ins. above ground, with brass cap mkd.

T 23 S	
R 8 W R 7 W	
S 24	S 19
S 25	S 30
1964	

from which bearing trees mkd. by Brooks and Peterson

A fir, 24 ins. diam., bears N. 6° E., 406
lks. dist., with healed blaze.

A fir, 40 ins. diam., bears N. 39° W., 571
lks. dist., with healed blaze.

S. 89° 42' W., bet. secs. 24 and 25.

Ascend voer NE. slope, through dense reproduction and light
undergrowth.

6.30 Ridge, bears generally N. and S.; desc. over NW. slope, also
enter logged area, edge bears N. and S.

20.36 The E. 1/16 sec. cor. of secs. 24 and 25, monumented with an iron
post, 2½ ins. diam., firmly set, projecting 5 ins. above ground,
with brass cap mkd.

E 1/16	S 24
	S 25
	1964

from which the remains of bearing trees mkd. by Brooks and
Peterson

A fir stump, 30 ins. diam., bears N. 75° E.,
27 lks. dist., with healed blaze.

A fir stump, 33 ins. diam., bears S. 8° W.,
30 lks. dist., with healed blaze.

The corner is located in logged area, no suitable trees available.