

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 25,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

18243

CHAINS	
	<p style="text-align: center;">A white oak, 15 ins. diam., bears N. 12½° W., 43 lks. dist., with scribe marks ¼ 453 visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 8 W C ¼ S 25 1985</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 20' W., beginning new measurement.</p> <p>Descend over broken NW. slope.</p>
8.40	<p>Ravine, drains S. 35° W.; asc. over broken S. slope.</p>
19.97	<p>The center N 1/16 sec. cor. of sec. 25, established and recorded by Forrest Hales, Registered Land Surveyor No. 453, in 1978, and is accepted as the corner, monumented with an iron rod, 5/8 in diam., firmly set, projecting 4 ins. above ground, from which the remains of bearing trees mkd. by Hales:</p> <p style="padding-left: 40px;">A root hole, bears N. 66° E., 18 lks. dist., with a down fir alongside, 11 ins. diam., with healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 10 ins. diam., bears S. 84° W., 27 lks. dist., no marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 25 C 1985</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 49° E., 62 lks. dist., mkd. CN 1/16 S25 BT.</p> <p style="padding-left: 40px;">No other suitable trees available.</p> <p>The corner is located at NW. cor. of timber, edge bears E. and S. 10° W.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 33' W., beginning new measurement.</p> <p>Ascend over broken S. slope, across logged area.</p>
10.00	<p>Spur ridge, bears N. 70° E., and S. 70° W.; desc. over NW. slope.</p>
10.50	<p>Intersection of gravelled roads, 20 lks. wide, bears N. 17° E., N. 50° E., and S. 70° W.</p>
19.94	<p>The ¼ sec. cor. of secs. 24 and 25.</p>