

County Surveyor's Record, Douglas County, Oregon

18244

Subdivision of Section 25,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS													
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p>												
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S 25</td> <td style="text-align: center; padding: 0 5px;">$\frac{1}{4}$</td> <td style="padding: 0 5px;">S 30</td> </tr> <tr> <td style="padding: 0 5px;">R 8 W</td> <td style="text-align: center; padding: 0 5px;"> </td> <td style="padding: 0 5px;">R 7 W</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">T 23 S</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">1964</td> </tr> </table>	S 25	$\frac{1}{4}$	S 30	R 8 W		R 7 W	T 23 S			1964		
S 25	$\frac{1}{4}$	S 30											
R 8 W		R 7 W											
T 23 S													
1964													
	<p>from which the bearing trees mkd. by Brooks and Peterson</p>												
	<p style="padding-left: 40px;">A fir, 33 ins. diam., bears N. 9° E., 23 lks. dist., with healed blaze.</p>												
	<p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. $69\frac{1}{2}^{\circ}$ W., 106 lks. dist., with healed blaze.</p>												
	<p>S. $89^{\circ} 44'$ W., on the E. and W. center line of sec. 25.</p>												
	<p>Ascend over SE. slope, through moderate timber and undergrowth.</p>												
5.00	<p>Spur, slopes S. 45° E.; desc. over SW. slope.</p>												
12.40	<p>Ravine, drains S. 25° E.; asc. over SE. slope.</p>												
20.205	<p>Point for the center E $1/16$ sec. cor. of sec. 25.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="3" style="padding: 0 5px;"><u>E 1/16</u></td> </tr> <tr> <td style="padding: 0 5px;">C</td> <td style="text-align: center; padding: 0 5px;">S 25</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">1985</td> </tr> </table>	<u>E 1/16</u>			C	S 25	C	1985					
<u>E 1/16</u>													
C	S 25	C											
1985													
	<p>from which</p>												
	<p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 4° E., 70 lks. dist., mkd. CE $1/16$ S25 BT.</p>												
	<p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. $77\frac{1}{2}^{\circ}$ W., 33 lks. dist., mkd. CE $1/16$ S25 BT.</p>												
	<p>Continue ascent over SE. slope.</p>												
23.30	<p>Spur, slopes S.; desc. over NW. slope.</p>												
40.41	<p>The center $\frac{1}{4}$ sec. cor. of sec. 25.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $89^{\circ} 50'$ W., beginning new measurement.</p>												
	<p>Continue descent over NW. slope.</p>												
4.80	<p>Ravine, drains S.; asc. over SE. slope, also enter logged area, edge bears N. 40° E. and W.</p>												
19.885	<p>The center W $1/16$ sec. cor. of sec. 25, established by the Federal Highway Administration, in 1977, perpetuated and recorded, by Carey Weatherly, Registered Land Surveyor No. 1667, in 1980, for International paper Co., and is accepted as the corner, monumented with an iron rod, $\frac{1}{2}$ in. diam., firmly set, projecting 4 ins. above ground, alongside of which is a steel fence post, firmly set, projecting 4 ft. above ground, from which the bearing tree mkd. by the Federal Highway Administration:</p>												
	<p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. $30\frac{3}{4}^{\circ}$ W., 42 lks. dist., with healed blaze.</p>												
	<p>and bearing trees mkd. by Weatherly</p>												