

County Surveyor's Record, Douglas County, Oregon

18245

Subdivision of Section 25
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 11 ins. diam., bears S. 66° E., 40 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A fir, 20 ins. diam., bears S. 38½° W., 44 lks. dist., with scribe marks W 1/16 S25 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C } \quad \text{S } 25 \quad \text{C} \\ 1985 \end{array}$ </div> <p>Reset 5 ft. steel fence post alongside iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 47' W., beginning new measurement.</p> <p>Ascend over SE. slope, through moderate timber and undergrowth.</p>
6.80	Gravelled road, 20 lks. wide, bears N. 20° W. and S.
13.30	Gravelled road, 20 lks. wide, bears N. 25° W. and S. 60° E., in curve.
14.60	Spur, slopes S. 15° E.; desc. over SW. slope.
19.875	The ¼ sec. cor. of secs. 25 and 26.
	<p>From the center E 1/16 sec. cor. of sec. 25.</p> <p>N. 0° 07' W., on the N. and S. center line of the NE ¼ of sec. 25.</p> <p>Ascend over SE. slope, through moderate timber and undergrowth.</p>
6.00	Spur, slopes S. 30° W.; desc. over NW. slope.
19.50	Ravine, drains S. 85° W.; asc. over SW. slope.
19.97	Point for the NE 1/16 sec. cor. of sec. 25, at intersection with the E. and W. center line of the NE¼.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with bras cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{NE } 1/16 \quad \text{S } 25 \\ 1985 \end{array}$ </div> <p>from which</p> <p>A fir, 13 ins. diam., bears S. 62 3/4° E., 65 lks. dist., mkd. X BT.</p> <p>A fir, 13 ins. diam., bears S. 4 3/4° W., 28 lks. dist., mkd. NE 1/16 S25 BT.</p> <p>The corner is located at NW. cor. of timber, edge bears E. and W.</p> <p>Ascend over SW. slope, across logged area.</p>
26.40	Spur, slopes W.; desc. over NW. slope.
27.30	Gravelled road, 20 lks. wide, bears E. and W.
39.98	The E 1/16 sec. cor. of secs. 25 and 25.