

County Surveyor's Record, Douglas County, Oregon

18246

Subdivision of Section 25,
T. 23 S., R.8 W., Willamette Meridian, Oregon

CHAINS							
	<p>From the N 1/16 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr> <td colspan="2">N 1/16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 25</td> <td style="padding: 0 5px;">S 30</td> </tr> <tr> <td colspan="2">1964</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Brooks and Peterson</p> <p style="margin-left: 40px;">A white oak, 25 ins. diam., bears N. 45° E., 101 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir stump, 33 ins. diam., bears N. 62° W., 121 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="margin-left: 40px;">A fir, 32 ins. diam., bears S. 39 3/4° W., 143 lks. dist., mkd. N 1/16 S 25 BT.</p> <p>From this corner, United States Geological Survey triangulation station "KELLOGG 1953", bears N. 9° 20' 30" E., 11.45 chs. dist., monumented with a standard brass tablet, 3½ ins. diam., set in an iron post, 3 ins. diam., firmly set, projecting 4 ins. above ground, mkd. KELLOGG 1953.</p> <p>S. 89° 43' W., on the E. and W. center line of the NE¼ of sec. 25.</p> <p>Ascend over SE. slope, along N. edge of timber, through scattering timber and undergrowth.</p>	N 1/16		S 25	S 30	1964	
N 1/16							
S 25	S 30						
1964							
10.30	Spur, slopes S. 15° W.; desc. over SW. slope.						
20.28	The NE 1/16 sec. cor. of sec. 25.						
	Descend over Sw. slope, across logged area.						
40.56	The center N 1/16 sec. cor. of sec. 25.						
	<p>From the W 1/16 sec. cor. of secs. 25 and 36, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">W 1/16</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 36</td> </tr> <tr> <td colspan="2">1964</td> </tr> </table> </div> <p>from which the remains of a bearing tree mkd. by Brooks and Peterson</p> <p style="margin-left: 40px;">A fir stump, 22 ins. diam., bears S. 51½° W., 67 lks. dist., with healed blaze. (Record, 70 lks.)</p> <p>and a new bearing tree</p> <p style="margin-left: 40px;">A hemlock stump, 29 ins. diam., bears N. 38° E., 11 lks. dist., mkd. W 1/16 S25 BT.</p> <p>The corner is located in logged area, no other suitable trees available.</p> <p>N. 0° 07' W., on the N. and S. center line of the SW¼ of sec. 25.</p> <p>Descend over NE. slope, across logged area, through light undergrowth.</p>	W 1/16	S 25		S 36	1964	
W 1/16	S 25						
	S 36						
1964							