

# County Surveyor's Record, Douglas County, Oregon

18247

Subdivision of Section 25,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
0.70	Gravelled road, 25 lks. wide, bears N. 40° E. and S. 85° W., in curve.
14.00	Creek, 6 lks. wide, course S. 70° E., asc. over broken SE. slope.
16.70	Gravelled road, 25 lks. wide, bears N. 80° W. and S. 80° E.
19.99	Point for the SW 1/16 sec. cor. of sec. 25, at intersection with the E. and W. center line of the SW ¼.  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">SW 1/16 S 25 1985</div> from which bearing trees mkd. by the Federal Highway Administration, in 1977  A fir, 12 ins. diam., bears N. 56¼° E., 20½ lks. dist., with healed blaze.  A fir, 13 ins. diam., bears N. 59° W., 24 lks. dist., with healed blaze. I remark X at breast height.  The corner is located at S. edge of timber, bears E. and S. 40° W.  Ascend over SE. slope, through moderate timber.
32.00	Spur, slopes S. 50° E.; desc. over NE. slope.
40.01	The center W 1/16 sec. cor. of sec. 25.
	From the center S 1/16 sec. cor. of sec. 25.  S. 89° 48' W., on the E. and W. center line of the SW¼ of sec. 25.  Ascend over SE. slope, through moderate timber and undergrowth.
0.15	Spur, slopes S. 35° W.; desc. over broken SW. slope.
6.50	Creek, 5 lks wide, course S. 5° W.; asc. over SE. slope.
13.50	Spur, slopes S.; desc. over Sw. slope.
16.70	Ravine, drains S. 10° W.; asc. over broken SE. slope.
19.93	The SW 1/16 sec. cor. of sec. 25.  Ascend over SE. slope, through moderate timber.
21.30	Spur, slopes S. 10° W.; desc. over SW. slope.
23.40	Ravine, drains S. 15° W.; asc. over SE. slope.
25.50	Spur, slopes S.; desc. over SW. slope.
28.80	Gravelled road, 25 lks. wide, bears N. 40° W. and S. 20° E., in curve.
34.90	Creek, 3 lks. wide, course S. 70° E.; asc. over NE. slope.
39.85	The S 1/16 sec. cor. of secs. 25 and 26, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.