

County Surveyor's Record, Douglas County, Oregon

18248

Subdivision of Section 25
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	S 1/16 S 26 S 25 1964
	from which the remains of bearing trees mkd. by Brooks and Peterson
	A root hole, bears S. 70½° E., 32 lks. dist., with a down hemlock alongside, 14 ins. diam., with healed blaze.
	A cedar stump, 16 ins. diam., bears N. 43° W., 53 lks. dist., no marks visible.
	and new bearing trees
	A hemlock, 10 ins. diam., bears S. 37¼° E., 44½ lks. dist., mkd. S 1/16 S25 BT.
	A fir, 17 ins. diam., bears S. 38 ¾° W., 23½ lks. dist., mkd. S 1/16 S26 BT.
	From the center W 1/16 sec. cor. of sec. 25.
	N. 0° 12' W., on the N. and S. center line of the NW¼ of sec. 25.
	Descend over NE. slope, across logged area, through light undergrowth.
4.90	Ravine, drains S. 60° E; asc. over broken S. slope.
8.20	Gravelled road, 25 lks. wide, bears N. 80° W. and S. 80° E.
19.96	The NW 1/16 sec. cor. of sec. 25, established and recorded by Carey Weatherly, Registered Land Surveyor No. 1667, in 1980, for International paper Co., and is accepted as the corner, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	T 23 S R 8 W NW 1/16 S 25 1981
	from which the remains of bearing trees mkd by Weatherly
	A fir stump, 40 ins. diam., bears N. 49° E., 37 lks. dist., with scribe marks NW 1/16 S25 BT visible on open blaze.
	A fir snag, 16 ins. diam., bears N. 10° W., 27½ lks. dist., with scribe marks NW 1/16 S25 BT visible on open blaze.
	and a new bearing tree
	A fir, 17 ins. diam., bears N. 73° W., 62 lks. dist., mkd. NW 1/16 S25 BT.
	The corner is located at SE. cor. of timber, edge bears N. and W.
	<hr style="width: 20%; margin: 0 auto;"/> N. 0° 10' W., beginning new measurement.
	Ascend over S. slope. along E. edge of timber..
5.90	Spur ridge, bears E. and W.; desc. over NE. slope.