

# County Surveyor's Record, Douglas County, Oregon

18252

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 28 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey by Dennis Hathorn, in 1856)

Beginning at the  $\frac{1}{4}$  sec. cor. of secs. 2 and 11, perpetuated and recorded by H. L. Eppstein, Douglas County Surveyor, in 1930, and further perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1957, monumented with an iron post,  $1\frac{1}{2}$  ins. diam., projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS

T 28 S R 8 W

$\frac{1}{4}$   $\frac{2}{11}$

1957

OFFICE

from which the remains of an original bearing tree

A cedar stump, 62 ins. diam., bears N. 17° E.,  
18 lks. dist., with reverse scribe marks  $\frac{1}{4}$  S2  
visible on overgrowth. (Record, 16 lks.)

and the remains of the bearing trees mkd. by Eppstein

A fir, 28 ins. diam., bears S. 78° E.,  
30 lks. dist., with healed double blaze.

A root hole, bears N. 55° W., 21 lks. dist.,  
with a rotted fir log, 15 ins. diam., lying  
alongside, with healed double blaze.

and a new bearing tree

A fir, 11 ins. diam., bears N. 47° W., 52  
lks. dist., mkd.  $\frac{1}{4}$  S2 BT.

The corner is located in a wire fence line, bearing e. and W.

S. 89° 14' W., bet. secs. 2 and 11.

Ascend over NE. slope, through heavy timber and dense undergrowth, along a fence line.

15.20 Slope changes; continue to asc. over steep E. slope.

20.06 The W  $\frac{1}{16}$  sec. cor. of secs. 2 and 11, established and recorded by Ben B. Irving, Registered Civil Engineer No. 240, in 1939, and is accepted as the corner, monumented with an iron pipe, 48 ins. long, 2 ins. diam., loosely set, projecting 18 ins. above ground.

from which bearing trees mkd. by Irving

A cedar, 13 ins. diam., bears S. 20° E., 43 lks.  
dist., with scribe marks W  $\frac{1}{16}$  S11 B visible  
on a partially healed blaze.

A fir, 20 ins. diam., bears N. 19 $\frac{1}{2}$ ° W., 80  
lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

W  $\frac{1}{16}$   $\frac{S}{S}$   $\frac{2}{11}$

1985