

County Surveyor's Record, Douglas County, Oregon

18253

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Reset the iron pipe alongside and deposit a white "DEEP-1" magnetic marker at base of the stainless steel post.

The corner is located at end of wire fence line, extending E.

S. 89° 15' W., beginning new measurement.

Ascend over steep E. slope.

12.30 Slope changes; continue to asc. over broken SE. slope.

18.20 Top of ascent; desc. over SW. slope.

19.60 Ravine, drains S.; asc. over steep E. slope.

20.14 The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 1½ ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S	
S 3	S 2
S 10	S 11
R 8 W	
1957	

from which the remains of an original bearing tree

A root hole, bears N. 81° E., 39 lks. dist., with a down fir, 28 ins. diam., lying alongside, no marks remaining.

and bearing trees mkd. by Ben B. Irving, Registered Civil Engineer No. 240, in 1939, recorded by Roseberry, Berry, Popken, and Garrison, in 1969-73.

A fir, 46 ins. diam., bears N. 5° E., 81 lks. dist., with marks T28S R8W S2 BT visible on bark. (Record, 84 lks.)

A fir, 36 ins. diam., bears S. 21° E., 69 lks. dist., with marks T28S R8W BT visible on bark.

A cedar, 15 ins. diam., bears S. 78° W., 32 lks. dist., with healed double blaze.

and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1957

A cedar, 12 ins. diam., bears N. 43° E., 79 lks. dist., with healed blaze.

A cedar, 15 ins. diam., bears S. 46° E., 38 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, chinquapin, and alder; undergrowth, salal, Oregon grape, rhododendron, vine maple poison oak, fern, and grasses.