

# County Surveyor's Record, Douglas County, Oregon

18254

Subdivision of Section 11,  
T. 28 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

From the  $\frac{1}{4}$  sec. cor. of secs. 11 and 14, reestablished and recorded by H. L. Eppstein, Deouglas County Surveyor, in 1930, perpetuated and recorded by Floyd Frear, former Douglas County Surveyor, in 1954, by John M. Powell, Deputy County Surveyor, in 1970, and further perpetuated and recorded by Randall W. Smith, Deputy County Surveyor, in 1984, and is accepted as the best available evidence of the position of the original corner, monumented with Eppstein's steel rod. 1 in. diam., firmly set, projecting 2 ins. above ground, and with an iron post,  $1\frac{1}{2}$  ins. diam., projecting 8 ins. above ground, plumbed over the steel rod, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S R 8 W

$\frac{1}{4}$   $\frac{S 11}{S 14}$

1970

*FD  
R. DOLAN  
12/94 M/21-53*

from which bearing trees mkd. by Frear in 1954

a madrone, 18 ins. diam., bears N. 53° E.,  
37 lks. dist., with a healed blaze.

A fir, 29 ins. diam., bears S. 15° E., 77  
lks. dist., with a healed blaze.

and a bearing tree mkd. by Smith in 1984

A madrone, 12 ins. diam., bears N. 28° W., 63 lks. dist.,  
mkd.  $\frac{1}{4}$  S11 CS BT on a double blaze.

From this point, the cor. of secs. 11, 12, 13, and 14, bears East, 40.26 chs. dist., perpetuated and recorded by H. L. Eppstein, Douglas County Surveyor, in 1930, monumented with a steel rod,  $1\frac{1}{2}$  ins. diam., firmly set, projecting 3 ins. above ground, from which the remains of an original bearing tree:

A rotted oak root crown, bears N. 52° E.,  
37 lks. dist., no marks remaining.

and a bearing tree mkd. by Eppstein

A fir, 15 ins. diam., bears N. 39° W., 80  
lks. dist., with healed double blaze.

and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1957

A madrone, 8 ins. diam., bears N. 74° E., 16 $\frac{1}{2}$   
lks. dist., with healed blaze.

A madrone, 10 ins. diam., bears S. 70° E.,  
11 $\frac{1}{2}$  lks. dist., with healed double blaze.

A madrone, 11 ins. diam., bears S. 49° W.,  
34 lks. dist., with healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T 28 S R 8 W

$\frac{S 11}{S 14}$  |  $\frac{S 12}{S 13}$

1985

*FD OK  
R. DOLAN  
12-94 M/21-53*

Deposit the steel rod alongside the corner