

County Surveyor's Record, Douglas County, Oregon

18256

Subdivision of Section 11,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS													
	<p>From this point, the corner of wire fences, extending S. and E., bears N. 30° W., 0.48 chs. dist.</p> <p>From this same point, a monument of which I find no description, bears N. 19° 02' W., 0.70 chs dist., a steel axle, 1½ ins. diam., with a wheel hub, 6 ins. diam., attached to the top. projecting 2 ins. above ground, from which bearing trees not of record:</p> <p style="padding-left: 40px;">A fir stump, 33 ins. diam., bears S. 3° E., 25 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears N. 30° W., 23½ lks. dist., with healed blaze.</p> <p>An examination of Douglas County Survey File, Volume 14, Entry 58, (CS 14/58) indicates that this monument is at the position of E. and W. center line random point No. 6, established by H. L. Eppstein, Douglas County Surveyor, in 1930, during the subdivision of sec. 11, shown on page 9A of Volume 4 of the survey file, and not at the center of the section.</p> <p>Descend over steep N. slope.</p>												
40.50	Wire fence, bears E. and W.												
42.00	Dry creek bed, 3 lks. wide, drains E.; asc. over broken SW. slope.												
55.90	Dirt road, 15 lks. wide, bears N. 80° E. and S. 80° W.												
60.17	<p>Point for the center N 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr><td></td><td style="text-align: center;">C</td><td></td></tr> <tr><td style="text-align: center;">N 1/16</td><td style="text-align: center;"> </td><td style="text-align: center;">S 11</td></tr> <tr><td></td><td style="text-align: center;">C</td><td></td></tr> <tr><td></td><td style="text-align: center;">1985</td><td></td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 11 ins. diam., bears S. 52½° E., 33½ lks. dist., mkd. CN 1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 56 3/4° W., 64½ lks. dist., mkd. CN 1/16 S11 BT.</p> <p>Ascend over S. slope.</p>		C		N 1/16		S 11		C			1985	
	C												
N 1/16		S 11											
	C												
	1985												
79.00	Top of ascent, slopes E.; desc. over NE. slope.												
80.23	<p>The ¼ sec. cor. of secs. 2 and 11.</p> <p>From the ¼ sec. cor. of secs. 11 and 12, perpetuated and recorded by H. L. Eppstein, Douglas County Surveyor, in 1930, monumented with a steel rod, 24 ins. long, 1½ ins. diam., loosely set 18 ins. in the ground, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A decayed fir stump, 26 ins. diam., bears N. 85° W., 23 lks. dist., no marks remaining.</p> <p>and the remains of bearing trees mkd. by Eppstein</p> <p style="padding-left: 40px;">A fir stump, 41 ins. diam., bears N. 35° E., 183 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A rotted fir stump, 30 ins. diam., bears N. 44½° W., 145 lks. dist., no marks remaining.</p>												