

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 11, 18257
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T 28 S R 8 W ½ S 11 S 12 1985
	from which new bearing objects, no suitable trees available
	A fir stump, 29 ins. diam., bears S. 72¼° E., 66 lks. dist., mkd. X BT.
	A fir stump, 16 ins. diam., bears S. 88° W., 30 lks. dist., mkd. X BT.
	Reset the steel rod alongside, deposit a white "DEEP-1" magnetic marker at base of stainless steel post, and set a steel fence post alongside the corner.
	S. 89° 57' W., on the E. and W. center line of sec. 11.
	Descend over W. slope, through a logged area.
13.40	Asphalt road, 50 lks. wide, bears N. 30° E. and S. 30° W.
15.10	Creek, 5 lks. wide, course S. 20° W.; asc. over broken SE. slope.
19.50	Leave logged area, edge bears irregularly N. and S.; enter heavy timber and dense undergrowth.
19.99	From this point, a monument found, perpetuated, and recorded by Ronald R. Geisler, Registered Land Surveyor No. 1988, in 1984, bears North, 0.94 chs. dist., a steel axle, 1¼ ins. diam., with a wheel hub, 5 ins. diam., attached to the top, projecting 6 ins. above ground, from which the remains of a bearing tree recorded by Geisler:
	A fir stump, 30 ins. diam., bears S. 62° E., 8 lks. dist., with bark scribe marks 6 BT visible.
	and bearing trees mkd. by Geisler
	A fir, 6 ins. diam., bears N. 44½° E., 13 lks. dist., mkd. CE 1/16 S11 BT on a double blaze.
	A fir, 10 ins. diam., bears N. 36° W., 11 lks. dist., mkd. CE 1/16 S11 BT on a double blaze.
	An examination of Douglas County Survey File, Volume 14, Entry 58, indicates that this monument is at the position of E. and W. center line random point No. 13, established by H. L. Eppstein, Douglas County Surveyor, in 1930, during the subdivision of sec. 11, shown on page 9A of Volume 4 of the survey file, and not at the center E 1/16 sec. cor. position.
20.00	Wire fence, bears N. and S.
29.10	Power transmission line, bears N. 20° E. and S. 20° W.
32.00	Power transmission line, bears N. 20° E. and S. 20° W.
33.50	Slope changes; continue to asc. over NE. slope.
40.30	The center ½ sec. cor. of sec. 11.
	Ascend over NE. slope.
40.55	Wire fence, bears N. and S.

(cc 4/150)