

County Surveyor's Record, Douglas County, Oregon

18260

Subdivision of Section 11,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 15 ins. diam., bears N. 72 3/4° W., 8 1/2 lks. dist., with healed blaze.

and a new bearing tree

A fir, 10 ins. diam., bears S. 19° E., 20 lks. dist., mkd. N. 1/16 S11 BT.

The corner is in a wire fence line, bearing N. and S., and 20 lks. N. of the end of a wooden fence, extending E.

Subdivision of Section 22,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 28 S R 8 W
1/4 $\frac{S 22}{S 27}$
1973

from which bearing trees mkd. by Roseberry, Berry, Popken, and Garrison

A fir, 16 ins. diam., bears N. 5 1/2° E., 29 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears S. 38° W., 21 lks. dist., with healed blaze.

N. 0° 17' W., on the N. and S. center line of sec. 22.

Ascend over steep broken SE. slope, through heavy timber and dense undergrowth.

11.30 Spur, slopes SW.; desc. over NW. slope.

19.925 Point for the center S 1/16 sec. cor. of sec. 22.

Set a stainless steel post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
S 1/16 | S 22
C
1985

from which

A fir, 7 ins. diam., bears N. 46 1/4° E., 17 lks. dist., mkd. CS 1/16 S22 BT.

A grand fir, 30 ins. diam., bears S. 8° W., 17 lks. dist., mkd. CS 1/16 S22 BT.

Descend over NW. slope.

29.00 Ravine, drains NW.; asc. over SW. slope.

29.80 Top of ascent, slopes W.; desc. over broken NW. slope.

39.70 Bottom of descent, slopes W.; enter nearly level swampy area.