

County Surveyor's Record, Douglas County, Oregon

18261

Subdivision of Section 22,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS
39.85

The center 1/4 sec. cor. of sec. 22, established and recorded by N. E. Britt, Douglas County Surveyor, in 1880, Douglas County Survey File, Volume 1, Page 82, and is accepted as the corner, monumented with a sandstone, 4 x 4 ft., projecting 4 ft. above ground, no marks visible.

At the corner point

Set a brass tablet, 3 1/4 ins. diam., with a 3 1/2 in. stem, in a drill hole in the top center of the corner stone, mkd.

T 28 S R 8 W
C 1/4
S 22
1985

from which

An alder, 10 ins. diam., bears S. 78° E., 33 lks. dist., bark scribed C 1/4 S22 BT.

A cedar, 18 ins. diam., bears N. 76° W., 32 lks. dist., mkd. C 1/4 S22 BT.

N. 0° 05' W., beginning new measurement.

Ascend SE. slope.

- 2.30 Top of ascent, slopes SW.; desc. broken NE. slope.
- 19.50 Abandoned dirt road, 20 lks. wide, bears N. 80° W. and S. 80° E.
- 22.10 Slope change; desc. over broken NW. slope.
- 32.10 Bottom of descent, slopes W.; asc. over SW. slope.
- 39.10 Top of ascent, slopes W.; desc. over NW. slope.
- 40.35 The 1/4 sec. cor. of secs. 15 and 22, perpetuated and recorded by Floyd C. Frear, Douglas County Surveyor, in 1936, further perpetuated and recorded by James W. Byron, deputy County Surveyor, in 1957, and by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1 1/2 ins. diam., protruding 9 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
1/4 S 15
S 22
1966

from which the remains of an original bearing tree

A chinquapin stump, 25 ins. diam., bears S. 34° W., 13 1/2 lks. dist., with a healed blaze and scribe marks BT visible on a blaze made by Byron.

and the remains of a bearing tree mkd. by Frear

A fir stump, 36 ins. diam., bears S. 66° E., 21 lks. dist., bark scribed CS 1/4 S BT.

and a bearing tree mkd. by Byron

A fir, 9 ins. diam., bears N. 32° E., 38 lks. dist., with healed double blaze.

and new bearing trees